



GOLDBERG BROTHERS

BARN DOOR HARDWARE

DOOR GUIDES



One of the smallest but most important parts of any barn door installation is the door guide, sometimes called the floor guide. The door guide helps keep the door and rollers at the correct vertical angle for smooth operation and a long operational life. Goldberg Brothers makes several types of door guides to meet various installation requirements.

 1½" x 1½" x 1"		6001G-* (raw aluminum or 16 colors) 6005G (powder coated aluminum to match stainless steel hardware)	T-Guide The T-guide is included with most of our barn door hardware sets. It can also be purchased separately. This sturdy, powder-coated aluminum component fastens to the floor with included screws. It requires a ¼" x ¾" continuous mortised slot in the bottom of the door.
 ¾" x 1" x 1½" each		6001U-* (raw aluminum or 16 colors) 6005U (stainless steel) Also available: 6005UG (stainless steel for glass doors)	U-Guide The U-guide is a two-piece system that works with an unslotted door, such as one made with our Barn Door Edge Wrap. It can be positioned to fit any door thickness. The U-Guide fastens to the floor with included screws.
 1½" x 2" x 2" standard 1½" x 2" x 2½" long 1½" x 2" x 3¼" extra long		6001SW,-* 6001SWE,-*, 6001SWEX,-* (raw steel or 16 colors) 6005SW, 6005SWE, 6005SWEX (stainless steel) Also available: 6005SWG (stainless steel for glass doors)	Sidewall Bracket When it is not practical to mount a T-Guide or U-Guide to the floor, you can fasten either one of them to a Sidewall Bracket that attaches to the wall or baseboard. Sidewall Brackets are available in three sizes to fit a wide range of door widths. Mounting hardware is included.
 1½" x 1½" x 1¾" base 1½" x 1" x 1" adjustable guide		6001GA-* (raw steel or 16 colors) 6005GA (stainless steel)	All-in-One guide Our All-in-One guide can be used with slotted or unslotted doors and can be attached to the floor or the wall. It can be adjusted to fit as a T-guide for 1" to 4" slotted doors or as a U-guide for ¾" to 1" unslotted doors. Mounting screws and an adhesive-backed felt pad are included.
 1½" x 24" x 1"		6001G2-* (raw steel or 16 colors) 6005G2 (stainless steel)	24-inch T-Guide This extra-long T-guide can be used for special applications. It should not be installed in the doorway opening where it could cause a tripping hazard. Mounting screws are included. It requires a ¼" x ¾" continuous mortised slot in the bottom of the door.
 2" x ¾" x ½" each pin ⅛" x ¾" x 98" guide channel images not to scale		Continuous Floor Guide 6001FGC (clear anodized aluminum) Continuous Floor Guide Pins 6001FGP (black)	Continuous Floor Guide and Pins This door guide system can be mounted flush with the floor surface. The guide channel is not pre-cut or pre-drilled so you can customize it yourself. The pins attach to the bottom of an unslotted door with provided mounting screws.
1½" x 1¾" x 1½" for 1¾" thick door 1½" x 1¾" x 1¾" for 1¾" thick door 1½" x 1¾" x 2%" for 2%" thick door	 T-guide sold separately	60013GX, 60014GX, 60015GX (raw steel or 16 colors) 60053GX, 60054GX, 60055GX (stainless steel)	Bypass J-Guide This guide attaches to the inner door in a bypass configuration and acts like a T-guide for the outer door. It is available in three sizes for a wide range of door thicknesses. Mounting screws are included. It requires a ¼" x ¾" continuous mortised slot in the bottom of the outer door.

* See Goldberg Brothers Standard Series catalogs for color codes and samples.